

G:B:D:



•AUTOBOX

**OPERATORS FOR
COUNTERWEIGHT
OVERHEAD DOORS**





AUTOBOX

Irreversible electromechanical operators for counterweight overhead doors

The ideal product for counterweight overhead doors for both residential and condominium use. Elegant and compact, easy to install, equipped with courtesy light and opening and closing limit switches integrated.

The new reinforced mechanics makes it extremely robust, silent and reliable over time. Unlocking device for emergency manoeuvres integrated with possibility of connecting it to the door handle.

Thanks to the wide range of control units, the force and deceleration during opening and closing can be regulated to achieve the highest level of safety against crushing as required by the EN 12453 standards.

It is even easier for the 24 VDC version on which the optional battery kit can be installed, which allows opening and closing the door even in the event of a blackout.

Technical data	AUTOBOX3000	AUTOBOX3024
use	residential	heavy
frequency of use	30%	40%
motor power supply	● 230 Vac - 50/60 Hz	● 24 Vdc
power absorbed	200W	100W
degree of protection	IP40	IP40
leaf rotation speed	7.8°/s	5.6°/s
maximum torque	250 Nm	250 Nm
nominal torque	200 Nm	200 Nm
torque regulation	electronic	electronic
maximum leaf surface	7 m ²	7 m ²
operating temperature	-20°C +60°C	-20°C +60°C
thermal switch	140°C	-
built-in courtesy light	YES	YES
limit switch	2 - opening and closing	2 - opening and closing
operator weight	8.6 Kg	8.6 Kg

Accessories



Courtesy light

Body in anodised aluminium

Gears in steel and
bronze-aluminium

Unlocking device

Opening and closing limit
switch incorporated



 a **BANDINI INDUSTRIE** company



Associated



GIBIDI

GI.BI.DI. S.r.l.

Via Abetone Brennero, 177/B
46025 Poggio Rusco (MN) - ITALY
Tel. +39.0386.52.20.11
Fax +39.0386.52.20.31
info@gibidi.com

www.gibidi.com