

Door Contact DZ 73

Safety Switch, oblong version



Function and Range of Application

The door contact DZ 73 is a safety switch with positive contact and is used to control the close position of elevator doors or as a switch for locking mechanism on automatic doors. In design the DZ 73 is identical with the PZ 73, but has a longer structural shape. The door contact is actuated by contact bridges PZ 18, PZ 21; DZ 18; DZ 21; PZ 18SO or PZ 24. For the door contact PZ 24 the protection against accidental contact has to be considered separately.

Features

- authoritative judgement G 330 by the TÜV for EN 81
- level of protection IP 20 (finger protection)
- actuation direction may be conversed
- high contact safety by self-cleaning
- quite functioning
- very long service life
- pressure plate for secure fixation

Order Information Codes

DZ 73 - B	door contact, base side actuation
DZ 73 - D	door contact, cover side actuation
DZ 18	contact bridge lang, 18 mm high
DZ 21	contact bridge lang, 21 mm high
PZ 18	contact bridge, 18 mm high
PZ 21	contact bridge, 21 mm high
PZ 24	contact bridge, 24 mm high (<i>not protected against accidental contact</i>)
PZ 18SO	contact bridge special (diagonal), 18 mm high
DZ - U1	pad, 1 mm thick for DZ 18/21
DZ - A	marking device for contact bridge DZ 18/21



